

Please type a plus sign (+) inside this box → ☐

Approved for use through 09/30/2000. OMB 0651-0031
Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

0300

0420

+ H3

TRANSMITTAL FORM (to be used for all correspondence after initial filing)	Application Number	09/819,237
	Filing Date	March 28, 2001
	First Named Inventor	Hsu et al.
	Group Art Unit	
	Examiner Name	
Total Number of Pages in This Submission		Attorney Docket Number CCP-3342-B

ENCLOSURES (check all that apply)		
<input type="checkbox"/> Fee Transmittal Form <input type="checkbox"/> Fee Attached <input checked="" type="checkbox"/> Supplemental Amendment / Response <input type="checkbox"/> After Final <input type="checkbox"/> Affidavits/declaration(s) <input type="checkbox"/> Extension of Time Request <input type="checkbox"/> Express Abandonment Request <input type="checkbox"/> Information Disclosure Statement <input type="checkbox"/> Certified Copy of Priority Document(s) <input type="checkbox"/> Response to Missing Parts/ Incomplete Application <input type="checkbox"/> Response to Missing Parts under 37 CFR 1.52 or 1.53	<input type="checkbox"/> Assignment Papers (for an Application) <input type="checkbox"/> Drawing(s) <input type="checkbox"/> Licensing-related Papers <input type="checkbox"/> Petition Routing Slip (PTO/SB/69) and Accompanying Petition <input type="checkbox"/> Petition to Convert to a Provisional Application <input type="checkbox"/> Power of Attorney, Revocation Change of Correspondence Address <input type="checkbox"/> Terminal Disclaimer <input type="checkbox"/> Small Entity Statement <input type="checkbox"/> Request for Refund	<input type="checkbox"/> After Allowance Communication to Group <input type="checkbox"/> Appeal Communication to Board of Appeals and Interferences <input type="checkbox"/> Appeal Communication to Group (Appeal Notice, Brief, Reply Brief) <input type="checkbox"/> Proprietary Information <input type="checkbox"/> Status Letter <input checked="" type="checkbox"/> Additional Enclosure(s) (please identify below): Replacement Sheets; Redline Version; and Return Postcard
Remarks		

SIGNATURE OF APPLICANT, ATTORNEY, OR AGENT	
Firm or Individual name	Whyte Hirschboeck Dudek, S.C. Kristine M. Strodthoff
Signature	<i>Kristine M Strodthoff</i>
Date	April 19, 2001


CERTIFICATE OF MAILING			
I hereby certify that this correspondence is being deposited with the United States Postal Service as first class mail in an envelope addressed to: Assistant Commissioner for Patents, Washington, D.C. 20231 on this date: April 19, 2001			
Typed or printed name	Lynda S. Hargreaves		
Signature	<i>Lynda S Hargreaves</i>	Date	April 19, 2001

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.



~~38~~ 39. A curable thermoset resin composition, comprising:

(A) at least 5 wt.% of at least one unsaturated polyetherester resin at least partially end-capped with an aromatic polyol comprising at least one non-primary hydroxy group, the aromatic polyol represented by the formula



wherein Ar₁, Ar₂ and Ar₃ each independently represents an aromatic group; R₁, R₂ and R₃ each independently represents a non-aromatic predominantly hydrocarbyl group; each X and X' independently represents a hydrocarbylene group, a hydrocarbylidene group, a divalent heteroatom or group, an ester linkage, or a combination thereof; each X' can also represent a covalent bond; h and k each independently represent an integer equal to 0 or 1; j represents an integer in the range from 0 to 5; and m, n, and p each independently represent an integer in the range from 1 to 5, provided that at least one hydroxy group of formula (I) is a nonprimary hydroxy group;

(B) at least one unsaturated polyester resin having a number average molecular weight to the average number of double bonds per polymer molecule in the range from about 200 to about 400, in an amount such that the weight ratio of polyester resin (B) to polyetherester resin (A) is in the range from about 10:90 to about 90:10;

(C) about 10 to about 70 wt.% of at least one vinyl monomer; and


(D) at least one curing agent.

~~39~~ 40. The composition according to Claim ~~38~~ 39, wherein, in the aromatic polyol, Ar₁, and Ar₂ and Ar₃ when present, each represent a phenylene ring.

~~40~~ 41. The composition according to Claim ~~38~~ 39, wherein, in the aromatic polyol, each X, when present, represents a hydrocarbylene or hydrocarbylidene group and each X' represents a hetero atom.

~~41~~ 42. The composition according to Claim ~~38~~ 39, wherein, in the aromatic polyol, h is 0.


~~42~~ 43. The composition according to Claim ~~41~~ 42, wherein the aromatic polyol comprises at least one primary hydroxy group and is represented by the formula:



wherein R₄ to R₇ each independently represent a hydrogen atom or a hydrocarbyl group, provided that at least one hydroxy group is a nonprimary hydroxy group.

~~43~~ 44. The composition according to Claim ~~38~~ 39, wherein, in the aromatic polyol, h is 1.

~~44~~ 45. The composition according to Claim ~~43~~ 44, wherein the aromatic polyol comprises at least one primary hydroxy group and is represented by the formula:



wherein each of R_8 to R_{13} represent a hydrogen atom or a predominantly hydrocarbyl group, provided that at least one of R_8 and R_9 is not an hydrogen atom, X represents $-(CH_3)_2-$, $-S-$ or $-O-$, and m and n represent integers which individually are in the range from 1 to 5.

~~45~~ 46. The composition according to Claim ~~44~~ 45, wherein the aromatic polyol is a propylene oxide adduct of bisphenol A.

~~46~~ 47. The composition according to Claim ~~38~~ 39, wherein, in the aromatic polyol, h is 1 and j is in the range from 1 to 5.

~~47~~ 48. The composition according to Claim ~~46~~ 47, wherein X is a methylene, alkylene or alkylidene group.

~~48~~ 49. The composition according to Claim ~~46~~ 47, wherein the aromatic polyol is an alkoxyated novolac-type polymer.

~~49~~ 50. The composition according to Claim ~~46~~ 47, wherein the aromatic polyol is a propoxylated novolac-type polymer.

~~50~~ 51. The composition according to Claim ~~38~~ 39, wherein the at least one unsaturated polyetherester resin comprises the reaction product of at least one polyether and at least one ethylenically unsaturated anhydride or dicarboxylic acid wherein the anhydride or dicarboxylic acid are inserted into carbon-oxygen bonds of the polyether.

~~51~~ 52. The composition according to Claim ~~50~~ 51, wherein the polyether is a polyether glycol having an average hydroxyl functionality of about 2 to about 6, a hydroxyl number of about 28 to about 260 mg KOH/g, and a number average molecular weight of about 400 to about 12,000.

~~52~~ 53. The composition according to Claim ~~38~~ 39, wherein the unsaturated polyester resin (B) is derived from at least dicyclopentadiene, an unsaturated carboxylic anhydride, and a glycol.

~~53~~ 54. The composition according to Claim ~~38~~ 39, wherein the vinyl monomer (C) comprises styrene.

~~54~~ 55. The composition according to Claims ~~38~~ 39, wherein the curing agent (D) comprises a catalyst system comprising a free radical initiator and an accelerator.

~~55~~ 56. The composition according to Claim ~~38~~ 39, further comprising at least one aromatic vinyl ester resin.

~~56~~ 57. The composition according to Claim ~~55~~ 56, wherein the at least one aromatic vinyl ester comprises a reaction product of epichlorohydrin and bisphenol A, which is further reacted with a vinyl acid.

~~57~~ 58. The composition according to Claim ~~55~~ 56, wherein the at least one aromatic vinyl ester comprises the reaction product of epichlorohydrin with a novolac-type resin, which is further reacted with a vinyl acid.

~~58~~ 59. The composition according to Claim ~~38~~ 39, further comprising a second unsaturated polyetherester resin other than the unsaturated polyetherester resin (A).

~~59~~ 60. The composition according to Claim ~~58~~ 59, wherein the second unsaturated polyetherester resin comprises an unsaturated polyester resin end-capped with at least one end-capping compound selected from the group consisting of dicyclopentadiene, an epoxy-containing compound, and combinations thereof.

~~60~~ 61. An intermediate in the form of a sheet for making a skin laminate, the intermediate comprising reinforcing fibers and the curable thermoset resin composition of Claim ~~38~~ 39.

~~61~~ 62. A gel coated polymer laminate comprising at least one fiber-reinforced polymer layer, at least one gel coat layer, and at least one thermoset resin layer interposed between the at least one fiber-reinforced polymer layer and the at least one gel coat layer, wherein the at least one thermoset resin layer comprises the skin laminate intermediate of Claim ~~60~~ 61, wherein the curable thermoset resin composition is cured.

~~62~~ 63. The gel coated laminate of Claim ~~61~~ 62, wherein the fiber-reinforced polymer layer comprises a reinforcing fiber and a polyester resin.

~~63~~ 64. The gel coated laminate of Claim ~~61~~ 62, wherein the ratio of the average thickness of the at least one fiber-reinforced polymer layer and the average thickness of the at least one thermoset resin layer is about 6:1 to about 2:1.

~~64~~ 65. A fiber-reinforced polymer composite comprising a cured composition comprising the curable thermoset resin composition of ~~Claim 38~~ Claim 39, and a reinforcing fiber.

~~65~~ 66. A gel coated fiber-reinforced polymer comprising the fiber-reinforced polymer composite of Claim ~~64~~ 65 and a gel coat.


~~66~~ 67. A gel coated polymer laminate comprising at least one fiber-reinforced polymer layer, at least one gel coat layer, and at least one thermoset resin layer interposed between the at least one fiber-reinforced polymer layer and the at least one gel coat layer, wherein the at least one thermoset resin layer comprises the curable thermoset resin composition of Claim ~~38~~ 39.

~~67~~ 68. The gel coated polymer laminate of Claim ~~66~~ 67, wherein the fiber-reinforced polymer layer comprises a reinforcing fiber and a polyester resin.

~~68~~ 69. The gel coated polymer laminate of Claim ~~66~~ 67, wherein the ratio of the average thickness of the at least one fiber-reinforced polymer layer and the average thickness of the at least one thermoset resin layer is about 6:1 to about 2:1.

~~69~~ 70. A curable thermoset resin composition, comprising:

(A) at least 5 wt.% of at least one unsaturated polyetherester resin at least partially end-capped with an aromatic polyol and the reaction product of at least one acid-terminated unsaturated polyetherester resin and at least one aromatic polyol having at least one non-primary hydroxy group; the at least one aromatic polyol represented by the formula:



wherein Ar₁, Ar₂ and Ar₃ each independently represents an aromatic group; R₁, R₂ and R₃ each independently represents a non-aromatic predominantly hydrocarbyl group; each X and X' independently represents a hydrocarbylene group, a hydrocarbylidene group, a divalent hetero atom or group, an ester linkage, or a combination thereof; each X' can also represent a covalent bond; h and k each independently represent an integer equal to 0 or 1; j represents an integer in the range from 0 to 5; and m, n, and p each independently represent an integer in the range from 1 to 5, provided that at least one hydroxy group of formula (I) is a nonprimary hydroxy group;


(B) at least one unsaturated polyester resin having a number average molecular weight to the average number of double bonds per polymer molecule in the range from about 200 to about 400, in an amount such that the weight ratio of polyester resin (B) to polyetherester resin (A) is in the range from about 10:90 to about 90:10;

(C) about 10 to about 70 wt.% of at least one vinyl monomer; and

(D) at least one curing agent.

~~70~~ 71. A method for making a curable thermoset resin composition, comprising combining:

(A) at least 5 wt.% of at least one unsaturated polyetherester resin at least partially end-capped with an aromatic polyol, the aromatic polyol comprising at least one non-primary hydroxy group and represented by the formula:



wherein Ar₁, Ar₂ and Ar₃ each independently represents an aromatic group; R₁, R₂ and R₃ each independently represents a non-aromatic predominantly hydrocarbyl group; each X and X' independently represents a hydrocarbylene group, a hydrocarbylidene group, a divalent heteroatom or group, an ester linkage, or a combination thereof; each X' can also represent a covalent bond; h and k each independently represent an integer equal to 0 or 1; j represents an integer in the range from 0 to 5; and m, n, and p each independently represent an integer in the range from 1 to 5, provided that at least one hydroxy group of formula (I) is a nonprimary hydroxy group;


(B) at least one unsaturated polyester resin having a number average molecular weight to the average number of double bonds per polymer molecule in the range from about 200 to about 400, in an amount such that the weight ratio of polyester resin (B) to polyetherester resin (A) is in the range from about 10:90 to about 90:10;

(C) about 10 to about 70 wt.% of at least one vinyl monomer; and

(D) at least one curing agent.

~~71~~ 72. An intermediate for making a curable thermoset resin composition comprising

(A) at least 5 wt.% of at least one unsaturated polyetherester resin at least partially end-capped with an aromatic polyol, the aromatic polyol comprising at least one non-primary hydroxy group and represented by the formula:



wherein Ar₁, Ar₂ and Ar₃ each independently represents an aromatic group; R₁, R₂ and R₃ each independently represents a non-aromatic predominantly hydrocarbyl group; each X and X'

independently represents a hydrocarbylene group, a hydrocarbylidene group, a divalent heteroatom or group, an ester linkage, or a combination thereof; each X' can also represent a covalent bond; h and k each independently represent an integer equal to 0 or 1; j represents an integer in the range from 0 to 5; and m, n, and p each independently represent an integer in the range from 1 to 5, provided that at least one hydroxy group of formula (I) is a nonprimary hydroxy group;


(B) at least one unsaturated polyester resin having a weight ratio of the number average molecular weight to the average number of double bonds per polymer molecule in the range from about 200 to about 400, in an amount such that the weight ratio of polyester resin (B) to polyetherester resin (A) is in the range from about 10:90 to about 90:10; and

(C) about 20 to about 50 wt.% of at least one vinyl monomer.


~~72~~ 73. The intermediate according to Claim ~~71~~ 72, further comprising a second unsaturated polyetherester resin other than the unsaturated polyetherester resin (A).

~~73~~ 74. A curable thermoset resin composition, comprising:

(A) at least 5 wt.% of at least one unsaturated polyetherester resin at least partially end-capped with an aromatic polyol comprising at least one primary hydroxy group, the aromatic polyol represented by the formula:



wherein R₄ to R₇ each independently represent a hydrogen atom or a hydrocarbyl group, provided that at least one hydroxy group is a nonprimary hydroxy group, or



wherein each of R_8 to R_{13} represent a hydrogen atom or a predominantly hydrocarbyl group, provided that at least one of R_8 and R_9 is not an hydrogen atom, X represents $-\text{C}(\text{CH}_3)_2$, $-\text{S}-$ or $-\text{O}-$, and m and n represent integers which individually are in the range from 1 to 5, or comprises an aromatic polyol prepared by alkoxyating a novolac-type polymer;

(B) at least one unsaturated polyester resin having a number average molecular weight to the average number of double bonds per polymer molecule in the range from about 200 to about 400, in an amount such that the weight ratio of polyester resin (B) to polyetherester resin (A) is in the range from about 10:90 to about 90:10;

(C) about 10 to about 70 wt.% of at least one vinyl monomer; and

(D) at least one curing agent.

~~74~~ 75. The composition according to Claim ~~73~~ 74, wherein the unsaturated polyester resin (B) is derived from at least dicyclopentadiene, an unsaturated carboxylic anhydride, and a glycol; the at least one vinyl monomer (C) comprises styrene; and the at least one curing agent (D) comprises a catalyst system comprising a free radical initiator and an accelerator.

~~75~~ 76. The composition according to Claim ~~73~~ 74, further comprising at least one aromatic vinyl ester resin.

~~76~~ 77. An intermediate in the form of a sheet for making a skin laminate comprising reinforcing fibers and the curable thermoset resin composition according to Claim ~~73~~ 74.

~~77~~ 78. A fiber-reinforced polymer composite comprising a cured composition comprising the curable thermoset resin composition of Claim ~~73~~ 74 with a reinforcing fiber.

~~78~~ 79. A gel coated fiber-reinforced polymer comprising the fiber-reinforced polymer composite of Claim ~~77~~ 78 and a gel coat.

~~79~~ 80. A method for reducing blistering of a gel coated fiber-reinforced polymer comprising:
applying a curable gel coat composition to a mold;
at least partially curing the gel coat composition;
applying at least one layer of at least one curable thermoset resin composition according to Claim ~~38~~ 39 to the at least partially cured gel coat composition;
at least partially curing the curable thermoset resin composition;
applying at least one fiber-reinforced polymer layer to the at least partially cured thermoset resin composition layer; and
curing the thermoset resin composition layer to form the gel coated fiber-reinforced polymer.

~~80~~ 81. An article produced by the method of Claim ~~79~~ 80.

~~81~~ 82. A method for reducing blistering of a gel coated fiber-reinforced polymer comprising:
applying a curable gel coat composition to a mold;
at least partially curing the gel coat composition;
applying at least one layer of the skin laminate intermediate of Claim ~~60~~ 61 to the at least partially cured gel coat composition;
at least partially curing the curable thermoset resin composition; and
applying at least one fiber-reinforced polymer layer to the at least partially cured thermoset resin composition layer; and
curing the thermoset resin composition layer to form the gel coated fiber-reinforced polymer.


~~82~~ 83. An article produced by the method of Claim ~~81~~ 82.

----- COMPARISON OF HEADERS -----

-HEADER 1-

USSN 09/819,237

SUPPLEMENTAL PRELIMINARY AMENDMENT (April 19, 2001)



----- COMPARISON OF FOOTERS -----

-FOOTER 1-

10 1

671817/Claims 671817v2/Claims

-FOOTER 2-

670694v1 Express Mail No. EL609566205US

3

This redlined draft, generated by CompareRite (TM) - The Instant Redliner, shows the differences between -

original document : C:\WINDOWS\TEMP\##DL01!.DOC

and revised document: G:\DOCS\KXS\0020\##DL02!.DOC

CompareRite found 85 change(s) in the text

CompareRite found 3 change(s) in the notes

Deletions appear as Overstrike text

Additions appear as Double Underline text